

KUMO TOTEM PENDANT (SUSPENDED)



A sculptural suspended pendant crafted from natural mulberry silk and plant fiber, composed of layered organic forms that create a striking vertical totem. The contrast between warm amber textures and softly translucent elements gives the fixture depth and a distinctive handcrafted character.

Kumo Totem Pendant is designed for high ceilings, stairwells, hotel lobbies, lounges, and statement residential spaces. Available in three heights, it can be used individually or arranged in dramatic multi-fixture compositions.

110-
277V

LED

IP20



PROJECT		MATERIAL: MULBERRY SILK + PLANT FIBER
SPEC TYPE		VOLTAGE: 110-277V
NOTES		LIGHTING: LED IP RATING: 20 APPLIANCE CLASS: I

110-277V	LED	IP20	
----------	-----	------	---



WE WELCOME ALL CUSTOM ORDERS

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

WWW.LOLALIGHTING.COM

OUTDOOR

TECHNICAL



DECORATIVE

Contact Us:

sales@gordonbullard.com

www.lolalighting.com

1 877-964-4646

 H: 31.50" (80 cm) Ø: 23.62" (60 cm)	-600-800
-600-1880	 H: 74.02" (188 cm) Ø: 23.62" (60 cm)
 H: 70.08" (178 cm) Ø: 23.62" (60 cm)	-600-1780
PROJECT	
SPEC TYPE	
NOTES	

HOW TO ORDER:

Example:
CODE: LL-9413-SN-600-800

1

DIMENSIONS:

-600-800

A) Diameter - Ø: 23.62" (60 cm)

B) Height - H: 31.50" (80 cm)

-600-1780

A) Diameter - Ø: 23.62" (60 cm)

B) Height - H: 70.08" (178 cm)

-600-1880

A) Diameter - Ø: 23.62" (60 cm)

B) Height - H: 74.02" (188 cm)

2

LIGHT SOURCE:

LED / 110-277V / 3000K

110-
277V

LED

IP20



WE WELCOME ALL CUSTOM ORDERS

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

WWW.LOLALIGHTING.COM

OUTDOOR

TECHNICAL

DECORATIVE

Contact Us:

sales@gordonbullard.com

www.lolalighting.com

1 877-964-4646